

---

## VOLTRONIC® 5W40 Motor oil

---

Ultra performance Synthetic motor oil designated for high performance engines, providing:

- Smooth running engine.
- EC (Energy Conservation).
- Long life.
- Ultimate engine protection.

### Country of Origin

Germany

### Accreditation / approval

Daimler AG Germany norm. 229.3

Volkswagen AG Germany norm 502.00 and 505.00

DIN EN ISO 9001:2000

### Specification

Exceed specifications:

ACEA A5/B1/B4

API SM/CJ4

### Application

Use for high performance gasoline and diesel engine with and without Turbocharged.

Mercedes-Benz 229.3

VW / Audi 502.00 and 505.00

BMW long life

Porsche performance

Performance motoroil for OPEL VOLVO SAAB RENAULT PEUGEOT CITROEN

SKODA ALFA ROMEO FIAT LEXUS TOYOTA HONDA NISSAN MITSUBISHI

MAZDA FORD CHRYSLER HYUNDAI KIA SSANGYONG & etc.

### Chemical Properties

State : Liquid

Colour : Yellow-tan

Odour : Characteristic odour

Solubility in water : Insoluble

Viscosity value : 89

Viscosity (Test method) : Kinematic viscosity in 10-6 m<sup>2</sup>/s at 40°C (ISO 3104/3105)

Boiling point/range°C : 160

Flammability limits %

Lower : 0.6

Upper : 6.5

Flash point°C : >220

Vapour pressure : <0.1 hPa

Relative density : 0.85

### Packaging

1 L, 5 L, 200 L and 1000 L.

Manufactured and packed in Germany by



ACT Aerosol Chemie Technik GmbH.  
Weidenweg 12, Bad Boll D-73087 Germany.  
[www.voltronic-germany.com](http://www.voltronic-germany.com)