

VOLTRONIC® ATF 4K
Automatikgetriebe-öl (Automatic Transmission Fluid)
Servolenkung-öl (Power Steering Fluid)

High performance ATF (Automatic Transmission Fluid) with balance performances properties of:

- Anti wear
- Anti ageing
- Anti friction
- Corrosion inhibitor

Universal use for:

- Automatic Transmission.
- Power Steering (heavy duty).
- Hydraulic System.

Country of Origin

Germany

Accreditation / approval

DIN EN ISO 9001:2000

Physical & Chemical Properties

State	: Liquid
Color	: Red
Odor	: Characteristic odor
Solubility in water	: Insoluble
Viscosity	: Oil
Viscosity value	: 42
Viscosity test method	: Kinematic viscosity in 10-6 m ² /s at 40°C (ISO 3104/3105)
Flammability limits % (Lower)	: 0.6
Flammability limits % (Upper)	: 6.5
Flash point °C	: 165
Vapor pressure	: <0.1 hPa
Relative density	: 0.871

Direction of use

Exceed quality / replacement for standard:

- ZF TE-ML 14.
- DEXRON II-D and DEXRON III.
- Mercedes-Benz MB 236.6 and MB 236.7.
- Type A Suffix A (TASA).
- MAN 339 type D/F.
- Allison C3.
- FORD Type M2C 33F/G and Type M2C 166H.
- Suitable to replace all make of Europeans cars ATF (except CVT).
- Suitable to replace all make of Japanese cars ATF (except CVT).
- Suitable to replace all make of Korean cars ATF (except CVT).
- Suitable to replace all make of Americans cars ATF (except CVT).
- Suitable to replace all make vehicles power steering fluid.

Observe manufacturer manual for other application where not stated above.

Packaging

1 L, 25 L, 60 L, 200 L and 1000 L tote IBC.



Manufactured and packed in Germany by

ACT

Since 1964

ACT Aerosol Chemie Technik GmbH.
Weidenweg 12, Bad Boll D-73087 Germany.
www.voltronic-germany.com