

SAFETY DATA SHEET
VOLTRONIC DRY CLEAN FOAM DC70

Page 1
Issued: 18.03.2008
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: VOLTRONIC DRY CLEAN FOAM DC70

Product code: DC 70

Synonyms: SCHAUMREINIGER
POLSTERSCHAUM
SCHEIBENSCHAUM

Use of substance / preparation: Cleaner Foam

Company name: VOLTRONIC & ACT GmbH

Weidenweg 12
Bad Boll
D-73087
Germany
Tel: +49 7164 4016
Fax: +49 7164 5994
Emergency tel: +49 7164 4016
Email: info@voltronic-germany.com

2. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable.

Other hazards: In use, may form flammable / explosive dust-air mixture. Harmful if swallowed. Harmful if swallowed. Harmful in contact with skin. Irritating to eyes. Irritating to skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS

- Hazardous ingredients:** PROPAN-2-OL 10-30%
EINECS: 200-661-7 CAS: 67-63-0
[F] R11; [Xi] R36; [-] R67
- PROPAN/BUTAN 10-30%
CAS: 68131-75-9
[F+] R12
 - AMMONIA% <1%
EINECS: 215-647-6 CAS: 1336-21-6
[C] R34; [N] R50

4. FIRST AID MEASURES (SYMPTOMS)

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Consult a doctor.

[cont...]

SAFETY DATA SHEET
VOLTRONIC DRY CLEAN FOAM DC70

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing becomes bubbly, have the casualty sit and provide oxygen if available.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Water spray. Alcohol resistant foam. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Extremely flammable. Forms explosive air-vapour mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. Mechanically ventilate the spillage area whilst avoiding the formation of explosive concentrations - see section 9 of SDS.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Mix with sand or vermiculite.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

Storage conditions: Store in cool, well ventilated area. Ensure lighting and electrical equipment are not a source of ignition. Keep away from sources of ignition. Keep away from direct sunlight.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: PROPAN-2-OL
WEL (8 hr exposure limit): 999 mg/m³ WEL (15 min exposure limit): 1250 mg/m³

- PROPAN/BUTAN
WEL (8 hr exposure limit): 1000 WEL (15 min exposure limit): 4

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Hand protection: Protective gloves. Breakthrough time of the glove material > 4 hours.

Eye protection: Tightly fitting safety goggles.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Off-white

Odour: Characteristic odour

Solubility in water: Soluble

Viscosity: Non-viscous

Flammability limits %: lower: 2,0
 upper: 12,0
Flash point°C: <-1
Autoflammability°C: >340
Vapour pressure: 3,5b/20°C;6,5b/50°C
Relative density: 0,9
pH: 11

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat. Sources of ignition. Direct sunlight.

Materials to avoid: Strong oxidising agents.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: PROPAN-2-OL
IVN RAT LD50 1088 mg/kg
ORL MUS LD50 3600 mg/kg
ORL RAT LD50 5045 mg/kg
SCU MUS LDLO 6 gm/kg

- AMMONIA%
IVN MUS LD50 91 mg/kg
ORL RAT LD50 350 mg/kg
SCU MUS LDLO 160 mg/kg

12. ECOLOGICAL INFORMATION

Mobility: Non-volatile.

Persistence and degradability: Only slightly biodegradable.

Bioaccumulative potential: Bioaccumulation potential.

Other adverse effects: Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D9 Physico-chemical treatment not specified elsewhere in this Annex which results in final compounds or mixtures which are disposed of by means of any of the operations in this Annex (e.g. evaporation, drying, calcination, etc.).

R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1950 **ADR Class:** 2
Classification code: 5F
Shipping name: AEROSOLS (PROPAN/BUTAN; PROPAN-2-OL;)
Labelling: 2.1



IMDG / IMO

UN no: 1950 **Class:** 2
EmS: F-D,S-U **Marine pollutant:** .
Labelling: 2.1

IATA / ICAO

UN no: 1950 **Class:** 2
Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.



Risk phrases: R12: Extremely flammable.

Safety phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

S33: Take precautionary measures against static discharges.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Water hazard class: 1 Classification by VwVwS

Note: The regulatory information given above only indicates the principal regulations specifically

SAFETY DATA SHEET
VOLTRONIC DRY CLEAN FOAM DC70

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R11: Highly flammable.
R36: Irritating to eyes.
R67: Vapours may cause drowsiness and dizziness.
R12: Extremely flammable.
R34: Causes burns.
R50: Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.